

MSDS

(Posted 9/20/2012)

The attached MSDS sheets supersede all other MSDS sheets. Please file accordingly.

VENDOR: **PARKER A480**

STOCK# MFG# DESCRIPTION

G21-516	PP33 SEALING COMPOUND
G21-517	PP22 SEALING CORDS
G31-182	PP36 SEALING CORDS



Premium Elastic Sealant Cords

PP33 (P/N 475298); PP36 (P/N 475300)

MSDS Preparation Date (mm/dd/yyyy): 06/14/2012

Page 1 of 7

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product identifier : **Premium Elastic Sealant Cords**

Product Code(s) : PP33 (P/N 475298); PP36 (P/N 475300)

Product Use : Air conditioning and refrigeration sealer tapes for sealing around components.

Chemical Family : Mixture. This article is an off-white, gray, non-hardening sealing compound. It is supplied as a bead or tape on a release paper/film.

Supplier's name and address:
Parker Hannifin Corporation - Sporlan Division
206 Lange Drive
Washington, MO, U.S.A.
63090

Manufacturer's name and address:
Refer to Supplier

Information Telephone # : (636) 239 1111

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887 (Outside U.S.).

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS information: This product is not a WHMIS controlled product in Canada. This product is considered to be a 'manufactured article'. The Controlled Products Regulations (CPR) do not apply to manufactured articles [Hazardous Products Act Section 12(i)].

OSHA: This product is considered an 'article' under 29 CFR Part 1910.1200. This material is not classified as hazardous under OSHA regulations (29 CFR Part 1910.1200).

Emergency Overview : Solid article, no odour.
This article is an off-white, gray, non-hardening sealing compound. It is supplied as a bead or tape on a release paper/film.
No hazards resulting from the material as supplied. Burning produces obnoxious and toxic fumes.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation : May cause mild respiratory irritation at higher temperatures.

Skin : Direct skin contact may result in little or no irritation.

Eyes : Causes little or no irritation.

Ingestion : None expected, when used as intended. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Effects of long-term (chronic) exposure

: None known or reported by the manufacturer.

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: See ECOLOGICAL INFORMATION, Section 12.



Premium Elastic Sealant Cords

PP33 (P/N 475298); PP36 (P/N 475300)

MSDS Preparation Date (mm/dd/yyyy): 06/14/2012

Page 2 of 7

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	Wt.%
Calcium carbonate	1317-65-3	60.00 - 80.00
Talc	14807-96-6	3.00 - 7.00

SECTION 4 - FIRST AID MEASURES

- Inhalation** : Move to fresh air. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing has stopped, give artificial respiration. Obtain medical advice.
- Skin contact** : Remove contaminated clothing. Wash affected areas with soap and water. Wash contaminated clothing before re-use. If irritation or symptoms develop, seek medical attention.
- Eye contact** : Rinse with plenty of water. Lift upper and lower lids during flushing to ensure complete removal of chemical. If irritation persists, seek prompt medical attention.
- Ingestion** : Do NOT induce vomiting. Never give anything by mouth if victim is unconscious. If symptoms develop, seek medical attention.
- Notes For Physician** : Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

: Not flammable under normal conditions of use.

Flammability classification (OSHA 29 CFR 1910.1200)

: Not flammable.

Oxidizing properties

: None.

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

Suitable extinguishing media

: Use media suitable to the surrounding fire such as water fog or fine spray, alcohol foams, carbon dioxide and dry chemical.

Special fire-fighting procedures/equipment

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.

Hazardous combustion products

: Carbon oxides; formaldehyde; Nitrogen oxides (NOx); Sulphur oxides; phosphorus oxides ;Polycyclic aromatic hydrocarbons; Other unidentified organic compounds.

NFPA Rating

0 - Minimal 1 - Slight 2 - Moderate 3 - Serious
: *Health:* 0 *Flammability:* 0 *Instability:* 0 *Special Hazards:* None.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions

: Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. Individuals involved in the cleanup must wear appropriate personal protective equipment. For personal protection see section 8.

Environmental precautions

: Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.

Spill response/cleanup

: Remove all sources of ignition. Ventilate area of release. Stop the spill at source if it is safe to do so. Sweep up and shovel into suitable containers for disposal. Refer to Section 13 for disposal of contaminated material. Notify the appropriate authorities as required.

Prohibited materials

: None known.



Premium Elastic Sealant Cords

PP33 (P/N 475298); PP36 (P/N 475300)

MSDS Preparation Date (mm/dd/yyyy): 06/14/2012

Page 3 of 7

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
- US CERCLA Reportable quantity (RQ): None reportable.

SECTION 7 - HANDLING AND STORAGE

- Safe Handling procedures** : Provide adequate ventilation. Use personal protective equipment as required. Avoid breathing fumes. Avoid contact with skin and eyes. Keep away from extreme heat and flame. Keep away from incompatibles. Keep containers closed when not in use. Wash thoroughly after handling.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Store away from incompatible materials. Protect from damage.
- Incompatible materials** : Acids; Strong oxidizing agents; Bases; Reducing agents .
- Special packaging materials** : None known or reported by the manufacturer.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

<u>Exposure Limits</u>				
<u>Ingredients</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Calcium carbonate	N/Av	N/Av	15 mg/m ³ (total dust); 5 mg/m ³ (respirable)	N/Av
Talc	2 mg/m ³ (respirable)	N/Av	20 mppcf	N/Av

Ventilation and engineering measures

- : Provide adequate ventilation. If product is processed in a manner that generates dusts or fumes, provide mechanical ventilation to control airborne exposure levels.

Respiratory protection

- : Not required under normal conditions of handling. If product is processed in a manner that generates dusts or fumes, conduct air monitoring to assess the need for respiratory protection. If respiratory protection is warranted, wear NIOSH-approved respirators. Advice should be sought from respiratory protection specialists.

Skin protection

- : Not required under normal conditions of handling. For prolonged or repeated contact use protective gloves. Advice should be sought from glove suppliers.

Eye / face protection

- : Not required under normal conditions of handling. If product is processed in a manner that generates dusts or fumes, wear as appropriate: Safety glasses with side-shields; Goggles.

Other protective equipment

- : An eyewash station and safety shower should be made available in the immediate working area. Other equipment may be required depending on workplace standards.

General hygiene considerations

- : Avoid breathing fumes. Avoid contact with skin and eyes. Do not eat, drink or smoke when using this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.



Premium Elastic Sealant Cords

PP33 (P/N 475298); PP36 (P/N 475300)

MSDS Preparation Date (mm/dd/yyyy): 06/14/2012

Page 4 of 7

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Physical state** : solid
- Appearance** : Solid article. This article is an off-white, gray, non-hardening sealing compound. It is supplied as a bead or tape on a release paper/film.
- Odour** : odourless
- Odour threshold** : N/Av
- pH** : N/Av
- Boiling point** : N/Av
- Specific gravity** : 1.6
- Melting/Freezing point** : N/Av
- Coefficient of water/oil distribution** : N/Av
- Vapour pressure (mmHg @ 20° C / 68° F)** : N/Av
- Solubility in water** : insoluble
- Vapour density (Air = 1)** : N/Av
- Evaporation rate (n-Butyl acetate = 1)** : N/Av
- Volatile organic Compounds (VOC's)** : None.
- Volatiles (% by weight)** : Negligible
- Flash point** : None.
- Auto-ignition temperature** : N/Av
- Flash point Method** : N/Av
- Upper flammable limit (% by vol.)** : N/Av
- Lower flammable limit (% by vol.)** : N/Av
- Flame Projection Length** : N/Av
- Flashback observed** : N/Av
- Viscosity** : N/Av
- Absolute pressure of container** : N/Av

Section 10: Stability And Reactivity

- Stability and reactivity** : Stable under the recommended storage and handling conditions prescribed.
- Hazardous polymerization** : Hazardous polymerisation does not occur.
- Conditions to avoid** : Avoid heat and open flame. Avoid contact with incompatible materials. Do not use in areas without adequate ventilation.
- Materials To Avoid And Incompatibility** : Incompatible materials (see Section 7).
- Hazardous decomposition products** : None known, refer to hazardous combustion products in Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

- Target organs** : Eyes, skin, respiratory system and digestive system.
- Routes of exposure** : *Inhalation:* YES *Skin Absorption:* NO *Skin & Eyes:* YES *Ingestion:* YES
- Toxicological data** : There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Ingredients</u>	<u>LC₅₀(4hr)</u>	<u>LD₅₀</u>	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Calcium carbonate	N/Av	6450 mg/kg	N/Av
Talc	N/Av	N/Av	N/Av

- Carcinogenic status** : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.
- Reproductive effects** : Not expected to have other reproductive effects.
- Teratogenicity** : Not expected to be a teratogen.
- Mutagenicity** : Not expected to be mutagenic in humans.



Premium Elastic Sealant Cords

PP33 (P/N 475298); PP36 (P/N 475300)

MSDS Preparation Date (mm/dd/yyyy): 06/14/2012

Page 5 of 7

- Epidemiology** : Not available.
- Sensitization to material** : Not expected to be a skin or respiratory sensitizer.
- Synergistic materials** : Not available.
- Irritancy** : Causes little or no irritation.
- other important hazards** : None known.
- Conditions aggravated by overexposure** : None known or reported by the manufacturer.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity : As supplied, this product does not present a physical, health or environmental hazard.

 No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

- Mobility** : No data is available on the product itself.
- Persistence** : No data is available on the product itself.
- Bioaccumulation potential** : No data is available on the product itself.
- Other Adverse Environmental effects** : No data is available on the product itself.

SECTION 13 - DISPOSAL CONSIDERATIONS

- Handling for Disposal** : See Section 7 (Handling and Storage) for further details.
- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.

RCRA : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14: TRANSPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	Not regulated.	not regulated	none	
TDG Additional information	None.				
49CFR/DOT	None	Not regulated.	Not regulated	none	
49CFR/DOT Additional information	None.				
ICAO/IATA	None.	Not regulated.	Not regulated	none	
ICAO/IATA Additional information	None.				



Premium Elastic Sealant Cords

PP33 (P/N 475298); PP36 (P/N 475300)

MSDS Preparation Date (mm/dd/yyyy): 06/14/2012

Page 6 of 7

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reportable.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Not a hazard under normal conditions of use. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

US State Right to Know Laws:

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

Other U.S. State "Right to Know" Lists: The following chemicals are specifically listed by individual States: Calcium carbonate (MA, MN, NJ, PA, RI); talc (CA, MA, MN, NJ, PA, RI).

International Information:

Canadian WHMIS Classification: Refer to Section 2 for a WHMIS Classification for this product.

Canadian Environmental Protection Act (CEPA): All components of this product are on the Canadian DSL list.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16 - OTHER INFORMATION

HMIS Rating : * - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious
Health: 1 *Flammability:* 0 *Reactivity:* 0

Legend : ACGIH: American Conference of Governmental Industrial Hygienists
 CA: California
 CAS: Chemical Abstract Services
 CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
 CFR: Code of Federal Regulations
 DOT: Department of Transportation
 DSL: Domestic Substances List
 EPA: Environmental Protection Agency
 HMIS: Hazardous Materials Identification System
 HSDB: Hazardous Substances Data Bank
 IARC: International Agency for Research on Cancer
 Inh: Inhalation
 LC: Lethal Concentration
 LD: Lethal Dose
 MA: Massachusetts
 N/Ap: Not Applicable
 N/Av: Not Available
 NFPA: National Fire Protection Association



Premium Elastic Sealant Cords

PP33 (P/N 475298); PP36 (P/N 475300)

MSDS Preparation Date (mm/dd/yyyy): 06/14/2012

NIOSH: National Institute of Occupational Safety and Health
 NJ: New Jersey
 NTP: National Toxicology Program
 OSHA: Occupational Safety and Health Administration
 PA: Pennsylvania
 PEL: Permissible exposure limit
 RCRA: Resource Conservation and Recovery Act
 RI: Rhode Island
 RTECS: Registry of Toxic Effects of Chemical Substances
 SARA: Superfund Amendments and Reauthorization Act
 STEL: Short Term Exposure Limit
 TDG: Canadian Transportation of Dangerous Goods Act & Regulations
 TLV: Threshold Limit Values
 WHMIS: Workplace Hazardous Materials Identification System

References

- : 1. ACGIH, Threshold Limit Values and Biological Exposure Indices for 2012.
- 2. International Agency for Research on Cancer Monographs, searched 2012.
- 3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2012 (Chempendium, HSDB and RTECs).
- 4. Material Safety Data Sheet from manufacturer.
- 5. US EPA Title III List of Lists - October 2006 version.
- 6. California Proposition 65 List - March 16, 2012 version.

<p>Prepared for: Parker Hannifin Corporation - Sporlan Division 206 Lange Drive, Washington, MO 63090 U.S.A. Telephone: (636) 239-1111 www.parker.com Direct all enquiries to: Parker Hannifin Corp. - Sporlan Division.</p>	
<p>Prepared by: ICC The Compliance Center Inc. http://www.thecompliancecenter.com</p>	

DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by / obtained from Parker Hannifin Corp and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corp expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corp.

Preparation Date (mm/dd/yyyy)

: 06/14/2012

END OF DOCUMENT